

EPOXY & SYNTHETIC RESINS MATRIX



Selection Guide



Standards according to EN 1504 Norm	Product Packages	Type of Resin (form)	Injectable Epoxy Resin for the repair of Cracks (dry / without the presence of water)	Injectable PU Resin for the repair of Cracks (wet / with the presence of water)	Gravity filling form for the repair of Cracks	Patching material for concrete Repairs	Concrete Repairs with the use of patching Epoxy Mortar	Concrete Repairs vertically and above head	Beton contact system Epoxy binder / Adhesive / Bonding bridge for old & new concrete	Anchoring of rebars - threaded rods, or other steel items, etc.,			Adhesives for Beton-Plaque systems, etc.	Epoxy Bonding Adhesives for FRPs		Anti-dust Protection systems Primers for Flooring systems	For the production of Epoxy Resin Mortars by the addition of Quartz sand
										For vertical Rebars placed to horizontal concrete surfaces	For horizontal Rebars placed to vertical concrete surfaces and above head	Applicable to wooden members		Rigid Bonding products as Adhesives for several kind of materials (concrete, wood, metals)	Fast setting Adhesives for Chemical Anchors, Rebars, threaded rods, etc.		
1504-6	SINMAST PSF Anchor	-1,70 300 ml	GEL														
1504-6	SINMAST EPOXYFAST Anchor	-1,60 400 ml	GEL														
	BAL (Bonding Adhesive Liquid)	-1,10 4 kg 20 kg 200 kg	fluid														
1504-5	SINMAST J 12 (width of crack 1.0-3.0 mm)	-1,10 1 kg 2 kg	PIC														
1504-5	SINMAST J 20 (width of crack 1.0-3.0 mm)	-1,10 1 kg 2 kg	PIC														
1504-5	SINMAST J 20L (width of crack 1.0-3.0 mm)	-1,10 1 kg 2 kg	PIC														
1504-5	SINMAST J 24 (width of crack 0.1-1.0 mm)	-1,05 1 kg 2 kg	PIC														
1504-5	SINMAST J 26 (width of crack 0.1-1.0 mm)	-1,05 1 kg 2 kg	PIC														
1504-5	SINMAST J 158 (width of crack 0.1-0.4 mm)	-1,05 1 kg	PIC														
1504-4	SINMAST P 103	-1,05 1 kg 4 kg	PIC														
1504-4	SINMAST P 103 F (Fine)	-1,05 1 kg 4 kg	PIC														
1504-6	SINMAST P 103 FS Injection	-1,05 1 kg	PIC														
1504-4	SINMAST S2 (width of crack 1.0-3.0 mm)	-1,10 1 kg 2 kg 10 kg	PIC														
1504-5	SINMAST S2 L (width of crack 1.0-3.0 mm)	-1,10 1 kg 2 kg 10 kg	PIC														
1504-6	SINMAST S 2 W B	-1,05 1 kg 2 kg 10 kg	PIC														
1504-4	SINMAST S2 W	-1,10 1 kg 4 kg	PIC														
1504-4	SINMAST S2 W V	-1,15 1 kg 4 kg	PIC														
1504-4	SINMAST S 2 38 (Rapid)	-1,15 1 kg 2 kg 10 kg	PIC														
1504-4	SINPAST JJA (width of crack ≥ 3.0 & < 5.0 mm)	-1,55 1 kg 2 kg 10 kg	PIC														
1504-6	SINTOSUB (for application into sea-water and/or for underwater applications)	-1,05 10 kg	PIC														

SINTECNO Hellas SA
 4 Anaxagora str. (sideway Ilestou str.), P.O. Box 202,
 P.C. 19 400, Koropi - ATTIKA - GREECE
 Tel: (+30) 210 6026020 / Fax: (+30) 210 6624568
 e-mail: sintecno@otenet.gr - <http://www.sintecno.gr>

Type designed special for use during Winter time, in general

Type designed special for use during Summer time, in general

